

# Product datasheet

Specifications



APC Easy UPS On-Line, 6kVA/6kW, Rackmount 4U, 230V, Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, W/O rail kit

SRV6KRI

## Overview

<b>Presentation</b>	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
<b>Lead time</b>	Usually in Stock

## Main

<b>Main Input Voltage</b>	230 V
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated power in W</b>	6000 W
<b>Rated power in VA</b>	6000 VA
<b>Output connector type</b>	Hard wire 3-wire (1P + N + E) 1
<b>Number of rack unit</b>	4U
<b>Provided equipment</b>	1 USB cable 1 RS-232 configuration cable 2 rack mounting brackets 1 external battery pack 1 battery cable 1 user manual

## Batteries & Runtime

<b>Battery type</b>	Lead-acid battery
<b>Battery voltage</b>	192 V
<b>Number of battery filled slots</b>	0
<b>Number of battery free slots</b>	0
<b>Battery recharge time</b>	4 h
<b>Battery life</b>	3...5 year(s)
<b>Battery charger power</b>	235 W rated

## General

<b>Number of power module filled slots</b>	0
--	---

---

Number of power module free slots	0
-----------------------------------	---

---

Redundant	No
-----------	----

---

## Physical

---

Colour	Black (RAL 7010)
--------	------------------

---

Height	17.3 cm
--------	---------

---

Width	43.8 cm
-------	---------

---

Depth	71.0 cm
-------	---------

---

Net weight	61 kg
------------	-------

---

Mounting location	Front
-------------------	-------

---

Mounting preference	Lower
---------------------	-------

---

Mounting mode	Rack-mounted with kit
---------------	-----------------------

---

USB compatible	Yes
----------------	-----

---

Mounting position	Horizontal
-------------------	------------

---

## Input

---

Input voltage limits	110...300 V 60 % load 176...300 V full load
----------------------	--

---

Number of input connectors	1 hard wire 3-wire (1P + N + E)
----------------------------	---------------------------------

---

Network frequency	40...70 Hz auto sensing
-------------------	-------------------------

---

## Output

---

Maximum configurable power in VA	6000 VA
----------------------------------	---------

---

Maximum configurable power in W	6000 W
---------------------------------	--------

---

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

---

Harmonic distortion	1 %
---------------------	-----

---

UPS type	Double conversion online
----------	--------------------------

---

Wave type	Sine wave
-----------	-----------

---

Efficiency	94 % (full load)
------------	------------------

---

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
------------------------	--

---

Bypass type	Internal bypass (automatic and manual)
-------------	--

---

Crest factor	3 : 1
--------------	-------

---

## Conformance

---

Product certifications	CE UKCA EAC TISI
------------------------	---------------------------

---

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

---

## Environmental

---

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

---

Relative humidity	0...95 % non-condensing
-------------------	-------------------------

---

Operating altitude	0...3000 m
Ambient air temperature for storage	-15...60 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m
Acoustic level	55 dBA
Heat dissipation	1172 Btu/h
IP degree of protection	IP20

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes
Free slots	1
Control panel	Multifunction LCD status and control console

## Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	48.5 cm
Package 1 Width	83.6 cm
Package 1 Length	60 cm
Package 1 Weight	71 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	Yes

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Recommended replacement(s)