

Product datasheet

Specifications



APC Smart-UPS RT 1000VA, 230V, rackmount, 2U, 6x IEC 60320 & 2x IEC Jumpers outlets, w/network card

SURT1000RMXLI-NC

Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	700 W
Rated power in VA	1000 VA
Input Connection Type	IEC 60320 C14
Output connection type	6 IEC 60320 2 IEC Jumpers
Number of rack unit	2U
Battery type	Lead-acid battery
Provided equipment	CD with software Rack mounting support rails Smart UPS signalling RS-232 cable User manual

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Battery charger power	109 W rated
Battery power in VAh	328 VAh runtime
Battery life	3...5 year(s)
Replacement battery	RBC31

Battery option	SURT48RMXLBP 1 984 VAh SURT48RMXLBP 2 1640 VAh SURT48RMXLBP 3 2296 VAh SURT48RMXLBP 4 2952 VAh SURT48RMXLBP 5 3608 VAh SURT48RMXLBP 6 4264 VAh SURT48RMXLBP 7 5576 VAh SURT48RMXLBP 8 6888 VAh
-----------------------	---

Extended runtime	1
-------------------------	---

General

Number of power module free slots	0
--	---

Number of power module filled slots	0
--	---

Redundant	No
------------------	----

Physical

Colour	Black
---------------	-------

Height	8.5 cm
---------------	--------

Width	43.2 cm
--------------	---------

Depth	48.3 cm
--------------	---------

Net weight	23 kg
-------------------	-------

Mounting location	Front
--------------------------	-------

Mounting preference	Lower
----------------------------	-------

Mounting mode	Rack-mounted
----------------------	--------------

Two post mountable	0
---------------------------	---

USB compatible	No
-----------------------	----

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
--------------------------	--------------------------------

Input voltage limits	160...280 V
-----------------------------	-------------

Output

Maximum configurable power in W	700 W
--	-------

Harmonic distortion	Less than 3 %
----------------------------	---------------

Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
-------------------------	--

Crest factor	3 : 1
---------------------	-------

UPS type	Double conversion online
-----------------	--------------------------

Wave type	Sine wave
------------------	-----------

Bypass type	Built-in bypass
--------------------	-----------------

Maximum configurable power in VA	1000 VA
---	---------

Conformance

Product certifications	C-Tick CE GOST VDE
-------------------------------	-----------------------------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
------------------	--

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA
Heat dissipation	324 Btu/h
IP degree of protection	IP20

Communications & Management

Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Optional

Surge Protection and Filtering

Surge energy rate	420 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.6 cm
Package 1 Width	59.4 cm
Package 1 Length	63 cm
Package 1 Weight	27.8 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty 2 years repair or replace

Recommended replacement(s)