

# Product datasheet

Specifications



## APC Smart-UPS, Line Interactive, 2200VA, Tower, 230V, 8x IEC C13+2x IEC C19 outlets, Network Card, AVR, LCD, EcoStruxure IT Expert

SMT2200INCITE

### Overview

<b>Presentation</b>	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V
<b>Other Input Voltage</b>	220 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V
<b>Rated power in W</b>	1980 W
<b>Rated power in VA</b>	2200 VA
<b>Input Connection Type</b>	IEC 320 C20
<b>Output connection type</b>	8 IEC 320 C13
<b>Number of cables</b>	1
<b>Battery type</b>	Lead-acid battery
<b>Provided equipment</b>	USB cable

### Batteries & Runtime

<b>Additional information</b>	Configurable for 220 : 230 or 240 nominal output voltage
<b>Extended runtime</b>	0
<b>Number of battery filled slots</b>	0
<b>Number of battery free slots</b>	0
<b>Battery recharge time</b>	3 h
<b>Number of battery replacement quantity</b>	1
<b>Battery life</b>	3...5 year(s)
<b>Replacement battery</b>	<a href="#">RBC55</a>
<b>Battery power in VAh</b>	783 VAh runtime
<b>Battery charger power</b>	260 W rated

## General

Number of power module filled slots 0

Number of power module free slots 0

Redundant No

## Physical

Colour Black

Height 43.5 cm

Width 19.7 cm

Depth 54.4 cm

Net weight 48.8 kg

Mounting location Front

Mounting preference No preference

Mounting mode Not rack-mountable

Two post mountable 0

USB compatible Yes

## Input

Input voltage limits 151...302 V adjustable

Network frequency 50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion Less than 5 % at full load

Maximum configurable power in VA 2200 VA

Maximum configurable power in W 1980 W

Transfer time 6 ms typical : 10 ms maximum

UPS type Line interactive

Wave type Sine wave

Output frequency 47...53 Hz for 50 Hz nominal sync to mains

## Conformance

Product certifications CE

## Environmental

Acoustic level 45 dBA

Heat dissipation 275 Btu/h

Operating altitude 0...10000 ft

Ambient air temperature for operation 0...40 °C

Ambient air temperature for storage -15...45 °C

Storage altitude 0.00...15240.00 m

IP degree of protection	IP20
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rate	365 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	69.9 cm
Package 1 Width	76.2 cm
Package 1 Length	38.1 cm
Package 1 Weight	61.9 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available
----------	--

## Recommended replacement(s)