

Product datasheet

Specifications



APC Smart-UPS, Line Interactive,
2200VA, Rackmount 2U,
230V, 8x IEC C13+2x IEC C19
outlets, Network Card, AVR,
LCD, EcoStruxure IT Expert

SMT2200RMI2UNCITE


Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V
Main Output Voltage	230 V
Other Output Voltage	220 V
Rated power in W	1980 W
Rated power in VA	2200 VA
Input Connection Type	BS1363A British
Output connection type	8 IEC 320 C13
Number of rack unit	2U
Cable length	2.00 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	USB cable

Batteries & Runtime

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	RBC43 
Battery power in VAh	509 VAh runtime

Battery charger power	169 W rated
-----------------------	-------------

General

Number of power module filled slots	0
-------------------------------------	---

Number of power module free slots	0
-----------------------------------	---

Redundant	No
-----------	----

Physical

Colour	Black
--------	-------

Height	8.6 cm
--------	--------

Width	48 cm
-------	-------

Depth	68.3 cm
-------	---------

Net weight	42.31 kg
------------	----------

Mounting location	Front
-------------------	-------

Mounting preference	Lower
---------------------	-------

Mounting mode	Rack-mounted
---------------	--------------

Two post mountable	0
--------------------	---

USB compatible	Yes
----------------	-----

Input

Input voltage limits	151...302 V adjustable
----------------------	------------------------

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

Output

Maximum configurable power in VA	2200 VA
----------------------------------	---------

Maximum configurable power in W	1980 W
---------------------------------	--------

Transfer time	4 ms typical : 8 ms maximum
---------------	-----------------------------

UPS type	Line interactive
----------	------------------

Wave type	Sine wave
-----------	-----------

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

Conformance

Product certifications	CE
------------------------	----

Marking	GS Mark
---------	---------

Environmental

Acoustic level	55 dBA
----------------	--------

Heat dissipation	215 Btu/h
------------------	-----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

Ambient air temperature for storage	-15...45 °C
-------------------------------------	-------------

Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Free slots	1
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	375 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.4 cm
Package 1 Width	98 cm
Package 1 Length	60 cm
Package 1 Weight	49.73 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

Recommended replacement(s)