

# Product datasheet

Specifications



## APC Smart-UPS Line Interactive 2200VA, Lithium-ion, Rack, 2U, 230V, 8x IEC C13 + 1x IEC C19, SmartConnect+SmartSlot, AVR, LCD

SMTL2200RMI2UC

⚠ Coming soon

⚠ Launching in: October 2023

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage 230 V

Other Input Voltage 220 V  
240 V

Main Output Voltage 230 V

Other Output Voltage 220 V  
240 V

Rated power in W 1980 W

Rated power in VA 2200 VA

Input Connection Type IEC 60320 C20

Output connection type 8 IEC 60320 C13  
1 IEC 60320 C19

Number of rack unit 2U

Battery type Li-Ion (Lithium-Ion)

Provided equipment Rack mounting brackets  
Rack mounting support rails  
Screw  
Washer  
USB cable  
Ethernet patch cable

### Complementary

Software package SmartConnect software for remote power monitoring feature availability varies by terms of use

### Batteries & Runtime

Battery graph comments This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v

Extended runtime 0

Battery recharge time 2 h

Number of battery replacement quantity 1

Battery design life	8...10 year(s)
Battery power in VAH	330 VAh runtime
Battery charger power	216 W rated

## General

Product web sub-family	Cloud-enabled monitoring
Redundant	No

## Physical

Colour	Black with silver front bezel
Height	8.6 cm
Width	43.2 cm
Depth	68.3 cm
Net weight	33.3 kg
Mounting preference	Lower
Mounting mode	Rack-mounted
USB compatible	Yes

## Input

Input protection type	Circuit breaker
Input voltage limits	160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Crest factor	3 : 1
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1980 W
Transfer time	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Equipment protection policy	Lifetime : \$150000
-----------------------------	---------------------

## Environmental

Acoustic level	55 dB
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...7620.00 m
IP degree of protection	IP20

Relative humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing

## Communications & Management

Alarm	Audible and visible alarms
Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1
Communication port support	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use Alarm when on battery : distinctive low battery alarm

## Surge Protection and Filtering

Surge energy rate	739 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	45.8 cm
Package 1 Width	60 cm
Package 1 Length	98 cm
Package 1 Weight	41.5 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	Yes

## Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

## Recommended replacement(s)