

Product datasheet

Specifications



APC Smart-UPS X, Line Interactive, 1000VA, Rack/tower convertible 2U, 230V, 8x C13 IEC, SmartSlot, Extended runtime

SMX1000I

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage 230 V

Main Output Voltage 230 V

Rated power in W 800 W

Rated power in VA 1000 VA

Input Connection Type IEC 320 C14

Output connection type 8 IEC 320 C13
2 IEC Jumpers

Number of rack unit 2U

Cable length 1.83 m

Number of cables 1

Battery type Lead-acid battery

Provided equipment CD with software
Documentation CD
Installation guide
Rack mounting brackets
Removable support feet
Smart UPS signalling RS-232 cable
USB cable

Batteries & Runtime

Extended runtime 0

Number of battery filled slots 0

Number of battery free slots 0

Battery recharge time 3 h

Number of battery replacement quantity 1

Overcurrent protection 60 A

Battery life 3...5 year(s)

Replacement battery [APCRBC116](#)

Battery power in VAh	299 VAh runtime
Battery charger power	99 W rated
Battery option	SMX48RMBP2U 1 900 VAh SMX48RMBP2U 2 1500 VAh SMX48RMBP2U 3 2100 VAh SMX48RMBP2U 4 2700 VAh SMX48RMBP2U 5 3300 VAh

General

Number of power module filled slots	0
Number of power module free slots	0
Product web sub-family	Extended run
Redundant	No

Physical

Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	49 cm
Net weight	22.86 kg
Mounting preference	Lower
Mounting mode	Rack-mounted with kit
Two post mountable	1
USB compatible	No

Input

Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	800 W
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product certifications	CE RCM VDE EAC
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	40 dBA
Heat dissipation	82 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...45 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	62 cm
Package 1 Length	58.9 cm
Package 1 Weight	27.32 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty 3 years repair or replace (excluding battery) and 2 years for battery

Recommended replacement(s)